



## PROFESSIONAL LINE



### Protective Treatments

## MA 90

### Solvent-based, stain-resistant, color-enhancing treatment for natural stone and absorbent materials

**MA 90** is a solvent-based, stain-resistant, color enhancer with a semi-gloss satin finish suitable for natural stones with non-polished finishes and a medium to medium-high absorption degree.

**MA 90** provides the treated surface with a wet look with a semi-polished finish with excellent stain-resistant qualities.

#### BENEFITS

- ✓ UV resistant
- ✓ Certified safe for use on surfaces in contact with food
- ✓ Satin-finish
- ✓ It won't yellow overtime

#### USES

This product can be used on both indoor and outdoor surfaces. Suitable for use on Slate, sandstone, Basalt - Lava rock, Concrete tiles, Cotto, Granite, Limestone, Marble, Reconstituted (eco) stone, Porphyry, Quarzite, Terracotta, Travertine, and Tuff. The product is not suitable for use on polished surfaces

#### COVERAGE

15/20 m<sup>2</sup>/l

#### APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth

#### APPLICATION STEPS

##### Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **MA 90** to wet or damp surfaces.
- Apply **MA 90** to surfaces with a temperature between +5 and +40°C
- Any surfaces in direct proximity not being treated must be protected.

##### Application

*Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.*

- Apply an even, abundant coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated.
- Wait about 5-10 minutes and proceed to distribute any product excess on the application area, taking care to even them out with the same tool, until the finished surface is even and homogeneous. This operation may not be necessary on particularly absorbent surfaces.
- After no less than 4-6 hours from the application but in any case, on a completely dry surface, it is possible to buff up the polished effect of **MA 90** by dry buffing. This operation is performed by buffing the surface, dry, using a floor polisher (1.5 HP, 175 rpm) with a white or lambswool disc or wool-cotton attachment. Alternatively, on tops, upright surfaces, or small areas, dry polishing is possible with an hand polisher.



## PROFESSIONAL LINE



### APPLICATION STEPS

#### Drying Time

The product dries quickly, within 1-2 hours of the application.

#### Resume Surface Use

Resume the use of the surface after 4-6 hours from the application

### MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **MA 90**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **MA 90**, we recommend: **FABER 30** or **DETERFUG** according to the type of material
- To remove **MA 90** we recommend: **DEC 21** and/or **DECERA/P** depending on the material .

### INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrating water-repellent sealer, wait for this to dry completely before applying **MA 90**.
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +5 and +35°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.
- The product is not suitable for use on polished surfaces

### EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit.

### PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Clear
Odor	Solvent
Specific gravity a 20°C	840 ± 10 g/l
Flash Point (ASTM D 56)	< 21°C

### STORAGE

Keep the container tightly closed and store in a cool, dry place.

### SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

### PACKAGING

1 l bottles – 12 bottles per box  
5 l bottles – 4 bottles per box

### SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 7.0 – 17/10/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.