

PROFESSIONAL LINE



Stain Removal

NO OIL

Product for the removal of oil stains, and greasy residues.

NO OIL is a solvent-based stain remover to be used to extract and remove grease and oily stains from hard surfaces. Its thick consistency makes it ideal for vertical applications.

The product is effective against the following staining agents

- Food oil and greasy foods;
- · Mineral oil, engine oil, diesel, and lubricants
- Bituminous residues

BENEFITS

- ✓ Great stain-extractive action
- Easy application
- ✓ Suitable for vertical application

USES

This product can be used both indoors and outdoors.

Suitable for use on Marble-resin agglomerate, Quartz-resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Concrete tiles, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Polished porcelain tiles, Natural porcelain tiles, Textured porcelain tiles, Limestone, Marble, Exposed brick, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff.

APPLICATION EQUIPMENT

Brush, Spatula, Direct application

APPLICATION STEPS

Surface preparation

- Make sure to thoroughly clean the surface removing all dirt and dust from the surface
- Do not apply NO OIL on heated surfaces.
- Do not apply NO OIL on wet surfaces.
- If the surface has been waxed make sure to remove it
- All surfaces close by that are not to be treated must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Never mix NO OIL with other chemicals.
- Shake well before use.
- The product is ready to use. Pour the product straight onto the stain making sure to cover it completely.
- Let the product act on the surface until it is completely dry. Once dry the product will become a white powdery residue.
- Remove the powder residue using a soft-bristled broom or clean brush if treating porous material. On compact, non-absorbent materials, the residue can be removed with paper towels or a cloth.
- Once all powder residues have been removed, wipe the surface with a slightly damp cloth or mop and wait for it to dry before assessing the stain removal results.



PROFESSIONAL LINE



APPLICATION STEPS

- If the achieved result is not satisfactory, repeat the application process as described above. If the stain is mixed, it may be a good idea also to use another type of stain remover.
- When treating particularly porous surfaces, after stain removal, it may be necessary to remove any remaining powder trapped in the pores. To do this it is possible to use a wet vacuum cleaner, and a suitable extractive cleaner. In more difficult cases, it is possible to use a pressurized washer.

Resume Surface Use

After rinsing the surface with water, wait for the floor to dry completely before opening to foot traffic.

INSTRUCTIONS AND GUIDELINES

- Do not apply the product on a dirty surface
- Do not apply the product on wet surfaces
- Never mix with other chemicals
- Do not apply the product on heated surfaces
- Surfaces near by not to be treated must be protected
- To achieve an even result we recommend applying the stain remover by treating areas that are larger than the single stained portion.
- When using on recently laid or grouted surfaces, wait for the grout to cure completely.
- While applying the product the surface must not be exposed to direct sunlight.
- Before applying the product is necessary to take a preliminary test in order to evaluate the product's suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit

PHYSICAL-TECHNICAL DATA

Formula	Thick gel
Color	offwhite
Odor	Solvent
Flash point (ASTM D 56)	21°C
Specific gravity a 20°C	1065 ± 20 g/l

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 500 ml bottles – 12 bottles per box

SAFETY When applying the product, always use suitable personal protective equipment

and follow the product safety data sheet instructions with care.

Rev. 5.0 - 17/10/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.