



PROFESSIONAL LINE



Honing & Polishing

PRC

Water-based fluid to restore full-body polished porcelain tiles and glazed polished porcelain tiles

PRC is a water-based fluid to be used to restore defects on full-body polished porcelain tiles, glazed polished porcelain tiles, and glazed surfaces in general. The product has an ultra-fine micro-abrasive effect that will restore flaws and defects on surfaces such as:

- Slight abrasions
- Scratches
- Dulness
- Disuniformity
- General wear

PRC acts without changing the original look of the surface and it's also part of our GLAZED POLISHED TILES RESTORATION SYSTEM.

BENEFITS

- ✓ Versatile solution
- ✓ Restores the original appearance of the material without spoiling the surface
- ✓ Even looking results
- ✓ Water-based product.
- ✓ No layering defects

USES

This product can be used on both indoor and outdoor surfaces.
This product is suitable for use on Full-body polished porcelain tiles, Glazed polished porcelain tiles (Lappato), Glazed surfaces

COVERAGE

20/30 m²/kg

APPLICATION EQUIPMENT

Single disc machine with at least 1.5 HP; manual rotary brush.

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present. We suggest using our **DETERFUG** or our **FABER 30**, depending on the nature of the dirt and the surface type.
- We suggest applying the product on surface sections of 2 m² at a time.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Shake the bottle well before use and pour the 1-2 spoonful of product onto the surface to be treated. This amount is sufficient to treat a surface area of about 1-2 m².

MADE IN ITALY

100%



PROFESSIONAL LINE



APPLICATION STEPS

- Add a small amount of water to the cream.
- As soon as the water has been added to the cream, proceed to apply it to the surface using the single disc machine, equipped with a white pad. Continue with the single disc machine, taking care to cover the whole surface area evenly with the cream. Try to pass over each section of the floor the same number of times.
- During the application process, the mix must maintain its creamy consistency, and therefore, if it should become too dry, gradually add some drops of water.
- Continue to pass over the surface with the polisher until the desired result is achieved.
- Vacuum-up the residues from the surface and rinse with plenty of clean water.

Resuming the surface use

After carefully removing any residues and rinsing the surface with water, the floor can be opened for use.

MAINTENANCE PRODUCTS

- For the daily maintenance of a surface treated with **PRC**, we recommend: **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **PRC**, we recommend **FABER 30** or **DETERFUG**, according to the type of dirt and the material to be cleaned.

INSTRUCTIONS AND GUIDELINES

- Do not allow the product to dry during the application process. Frequently check consistency and add water as needed to return the product to its creamy state.
- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Thick liquid
Color	Light Blue
Odor	Lightly Scented
pH:	8 ± 0,6

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.



PROFESSIONAL LINE



PACKAGING

1 kg Bottle – 12 bottles per box
5 kg Bottle – 4 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 0.0 – 02/12/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%